

13579ROUS01U

Page 1 of 25

Privileged &amp; confidential

**TITLE: APPARATUS FOR MANAGING THE INSTALLATION OF  
SOFTWARE ACROSS A NETWORK****FIELD OF THE INVENTION**

5           The present invention relates to automated software installation, in particular to a method and to a device for installing software in a data network.

**BACKGROUND OF THE INVENTION**

Software deployment across a network is a time  
10 consuming task. When a network has a very large number of nodes, the installation of a software product on all the nodes or on a large subset of the nodes is done mostly manually, which is time consuming and prone to installation errors. This places network operators that  
15 manage large networks at a disadvantage when a software upgrade must be performed across the network. For example, it is estimated that performing a software upgrade on a network that contains in excess of 10,000 nodes may require no less than 10 months.

20

Accordingly, there is a need in the industry to provide solutions for automating, at least in part, the installation of software in a network such that the installation can be completed faster than what is done  
25 currently with existing methods.

**SUMMARY OF THE INVENTION**

In a broad aspect the invention provides a software installation manager for use in a data network. The data network includes a set of nodes having a topology  
30 characterized in that a message directed from a first node of the set to a third node of the set passes through a second node of the set.

13579ROUS01U

Page 2 of 25

Privileged &amp; confidential

The software installation manager includes a control entity that exchanges messages with individual nodes of the set for causing installation of at least one software product on the nodes of the set in parallel according to a  
5 non-blocking sequence. The non-blocking sequence is characterized in that the installation of a software product on one node of the set does not block the installation of the software product on another node of the set.

10

The principal advantage of this apparatus over prior art software installation techniques resides in the ability to conduct the installation of the software product in parallel across several nodes of a data network  
15 where messages directed to one node transit through another node. The ability to perform the software installation in a non-blocking fashion across the nodes significantly reduces the time required to deploy the software product, in particular when the deployment has to  
20 be made over a large number of nodes.

For the purposes of this specification, the expression "installation in parallel" does not imply that all the steps or stages of the installation of the  
25 software occur at the same time for all the nodes. Rather, this expression should be interpreted broadly to mean that a certain step of the installation process at one node happens at the same time the same step, or a different step of the installation process, is being  
30 conducted at another node.

For the purposes of this specification, the expression "software product" should be interpreted broadly to include application software, operating system

13579ROUS01U

Page 3 of 25

Privileged &amp; confidential

software, hardware drivers, software loaded on a hardware platform, software upgrades, and so on.

In a specific non-limitative example of  
5 implementation of the invention, the software installation manager is controlled by a network manager entity. When an operator initiates at the network manager entity a software upgrade process, say through a Graphical User Interface (GUI), the network manager issues control  
10 messages to the software installation manager. In response to the control messages, the control entity of the software installation manager issues messages to the nodes of the set where the software product is to be installed. The messages convey commands that direct the  
15 software installation on each node. The order of some of the commands is selected according to a non-blocking sequence, to avoid one node blocking the installation of the software product on another node. The non-blocking sequence can be fixed, having been previously established  
20 on the basis of the network topology in which the installation is performed. Alternatively, the non-blocking sequence is dynamically established to suit changing environments. At this end, the control entity has a node sequencing entity that determines the non-  
25 blocking sequence based on the number of communication hops between each node of the set of nodes and a point of reference in the data network.

One of the commands sent to the nodes of the set  
30 according to the non-blocking sequence is a command to cause the nodes to reboot. Usually, this is done to activate the software product being installed. The use of the non-blocking sequence prevents a situation where a message commanding a certain node to reboot fails to reach

13579ROUS01U

Page 4 of 25

Privileged &amp; confidential

its destination because the message is blocked by another node in the process of rebooting (a node in the process of rebooting loses message passing capability). Advantageously, the messages are sent such that at least  
5 some of the nodes of the set perform coincident rebooting and preferably all of the nodes of the set perform coincident rebooting. By "coincident", it is meant that when one node has reached some arbitrary phase of the rebooting process, at that same point in time another node  
10 is also undergoing rebooting. To be "coincident" the rebooting of the nodes needs not begin at the same time, end at the same time or reach certain phases at the same time.

15 The control entity keeps track of the progress of the software product installation on each node and documents relevant events in a log. The log is conveyed to the network manager such that the information can be displayed to the network operator.

20

The invention also provides a method for performing software product installation in a data network.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

A detailed description of examples of implementation  
25 of the present invention is provided hereinbelow with reference to the following drawings, in which:

Figure 1 is a functional block diagram of a data network including software installation managers according  
30 to an embodiment of the present invention;

Figure 2 is a more detailed block diagram of the software installation manager shown in Figure 1;

13579ROUS01U

Page 5 of 25

Privileged &amp; confidential

Figure 3 is block diagram of the software installation manager in accordance with a variant; and

5 Figure 4 is a flowchart illustrating the sequence of events taking place when the software installation manager shown in Figure 1 installs software at one or more nodes of the data network.

10 In the drawings, embodiments of the invention are illustrated by way of example. It is to be expressly understood that the description and drawings are only for purposes of illustration and as an aid to understanding, and are not intended to be a definition of the limits of  
15 the invention.

### **DETAILED DESCRIPTION**

Figure 1 illustrates a data network 10. The data  
20 network 10 transports digitized information such as data, voice or video among others. The data network includes a plurality of nodes connected to one another by communication links also called "hops". A single node is usually in the form of a workstation or server, while a  
25 communication link can be implemented by a physical signal conductor, such as a metal cable or optical fiber, or the air interface allowing a wireless transmission.

In one example of implementation, the data network 10  
30 may be a telecommunications network where the communication links are optical links that use the SONET communication protocol. The nodes may be designed to provide a message passing/routing functionality and signal

13579ROUS01U

Page 6 of 25

Privileged &amp; confidential

amplification in addition to other more specific tasks. The data network 10 includes a node 12 that implements a network manager 14. The network manager 14 is an entity at which a human operator can control the data network 10 through a user interface whose function is to receive operator commands and deliver information to the operator. Advantageously, the user interface is a Graphical User Interface (GUI). The user can enter commands through any suitable input device, such as a keyboard, pointing device, touch screen, voice commands or any other suitable device. Information delivered by the user interface is of visual nature presented on a screen. In addition, the visual information can be supplemented with audible information.

15

The network manager 14 makes available to the operator data descriptive of the network 10. In general, this data contains information about the structure of the network. In one specific example of implementation, the data descriptive of the network 10 contains information about the various nodes and subnetworks that form the data network 10. The information about the nodes and subnetworks may include the list of the nodes and subnetworks, namely their identifiers such as labels and/or IP addresses and the number of nodes in each subnetwork, among other type of information. The data descriptive of the data network 10 may also include information about the current software releases running on each node and subnetwork, the hardware components connected to each node and subnetwork, or any other suitable information.

25  
30

The information about the structure of the data network 10 is displayed to the operator through the user

13579ROUS01U

Page 7 of 25

Privileged &amp; confidential

interface. The manner with which the data descriptive of the network can be displayed by the user interface can vary widely. In a specific example, the user interface shows a list of subnetworks and their associated labels.

5 Optionally, the user can select any one of the entries in that list to expand the information associated with the entry and show additional details of the particular subnetwork, such as individual nodes of the subnetwork.

10 The data network 10 also comprises a plurality of Subnetwork Management (SM) nodes 16, 18. One function of the SM nodes 16, 18 is to direct the installation of a software product on a respective set of nodes. Figure 1 shows that the SM node 16 is associated with a set of  
15 nodes 20 while the SM node 18 is associated with a different set of nodes 22. The set of nodes 20 has four nodes namely nodes 24-30. The set of nodes 22 also has four nodes 31-36.

20 The topology of the sets of nodes 20 and 22 is such that messages directed to one node of a set transit through another node of the set. Examples of this topology includes a linear network, a ring network, a tree network and a network that is a combination of two or more  
25 of the previous categories, among others. The set of nodes 20 is constructed according to a linear network topology, while the set of nodes 22 is constructed according to a tree network.

30 Figure 2 provides a detailed functional block diagram of an SM node 16. The functional block diagram of the SM node 18 is identical. The SM node 16 performs the function a software installation manager 38 that is implemented as a program element executed by the computing

13579ROUS01U

Page 8 of 25

Privileged &amp; confidential

device forming the SM node 16. The program element exists physically on a computer readable storage medium. The memory in the computing device of the SM node 16 is an example of a computer readable storage medium. The  
5 computer readable storage medium may take different forms without departing from the spirit of the invention.

The software installation manager 38 includes two main components, namely a control entity 40 and an  
10 Input/Output port (I/O) 42 that constitutes a point through which the control entity 40 can exchange messages with the external world, such as the network manager 14, the nodes 24-30 or any other node of the data network 10. The control entity 40 includes two sub-components, namely  
15 a message generation entity 46 and a node sequencing entity 48. The main function of the message generation entity 46 is to produce the messages that are directed to the nodes 24-30 to direct the installation of the software product on them. The main function of the node sequencing  
20 entity 48 is to determine a non-blocking sequence according to which at least some steps of the software product installation will be made on the nodes 24-30, such that the installation of the software product on one node 24-30 blocks the installation of the software product on  
25 another node 24-30.

The embodiment of the software installation manager 38 shown in Figure 2 is under the direct control of the network manager 14. In this example the network manager  
30 14 is the master and the software installation manager 38 is the slave. The operator at the GUI of the network manager 14 commands the beginning of the software installation process. At this end, the network manager 14 will produce control messages that are sent to each SM



13579ROUS01U

Page 9 of 25

Privileged &amp; confidential

node 16, 18. When an SM node 16, 18 receives the control message, it initiates the local software installation process limited to the nodes under its control.

5 Figure 3 illustrates a variant of the software installation manager, identified by the reference numeral 50. The difference with the previous embodiment resides in the presence of a GUI interface 52 that allows an operator to locally control the software installation  
10 manager 50 rather than through the intermediary of the network manager 14. Evidently, both functionalities can be implemented together, such that the software installation manager can respond to the network manager 14 and also possess a GUI interface 52 for local control when  
15 such necessity arises.

A detailed example of operation of the software manager 38 will now be described in connection with the flowchart of Figure 4. At step 54, the operation starts.  
20 At step, 56 the operator enters commands on the user interface of the network manager 14 to select the particular software product that is to be installed. At step 58, the operator enters commands on the user interface to specify on which nodes of the data network 10  
25 the software products are to be installed. Assume for the sake of this example that nodes 24-30 and 31-36 are selected. At step 60, the network manager constructs control messages and forwards the control messages to SM nodes 16, 18. Each SM node 16, 18 receives a dedicated  
30 set of such control message(s), where each control message(s) specifies the software product to be installed, the source of the load files of the software product, the nodes on which the installation is to made, among other possible information.

13579ROUS01U

Page 10 of 25

Privileged &amp; confidential

At step 62, each SM node 16, 18 receives the control message(s) through I/O 42. Each SM node 16, 18 handles the control message(s) in the same way. For simplicity  
5 only the steps in connection with SM node 16 will be described and reference to the SM 18 will be made only to illustrate features unique to that node.

The installation of the software product performed  
10 under the direction of the SM node 16 can be generally divided in five main stages. Those stages are:

1. Order nodes into non-blocking sequence;
2. Download catalogue file from server to nodes;
3. Download load files from server;
- 15 4. Activate nodes to software product;
5. Commit nodes to software product.

It should be expressly noted that the above sequence of stages can be altered without departing from the  
20 invention. Such alterations include the omission of one or more steps, the addition of one or more steps or a change in the sequence of the steps.

At step 64, the node sequencing entity determines the  
25 non-blocking sequence according to which the installation of the software product is to be made. The non-blocking sequence can be established in several ways. A first possibility is to use a fixed, non-blocking sequence that has been predetermined according to the current node set  
30 topology. A second possibility is to dynamically determine the non-blocking sequence. This can be done by ordering the nodes 24-30 on the basis of the number of communication hops between the node and a certain point of reference. In this example, the point of reference is the

13579ROUS01U

Page 11 of 25

Privileged &amp; confidential

SM node 16. The number of communication hops to the nodes 30, 28, 26 and 24 is respectively 4, 3, 2 and 1. In the case of the SM 18, the point of reference is the SM node 18 and number of communication hops to the nodes 36, 34, 5 32 and 31 is respectively 3, 3, 2 and 1.

Several possibilities exist to establish the number of communication hops from a point of reference to a certain node. One such possibility is for the SM node 16 10 to obtain from the network manager 14 information on the topology of the data network 10, from which the information on the number of communication hops to a point of reference can be extracted. Another possibility for the SM node 16 is to send to each node 24-30 a query 15 message to prompt the node 24-30 to generate a response message indicative of the number of communication hops between the node and the point of reference.

Several possibilities exist as to the selection of 20 the point of reference. One possibility, mentioned earlier, is to consider the SM 16 as the point of reference. This is done because the configuration of the set of nodes 20 is such that messages exchanged between any one of the nodes 24-30 and the external world (a node 25 external to the set of nodes 20) must transit through the SM 16. A more complex situation arises when the set of nodes 20 is not restricted to communicate with the external world through a single node. Assume for the sake of this discussion that the set of nodes 20 can 30 communicate with the external world through two points of entry/exit, one being the SM node 16 and one being another node (not shown). If during the software installation process, messages directed to the nodes 24-30 will transit through either one of the points of entry/exit then the

13579ROUS01U

Page 12 of 25

Privileged &amp; confidential

establishment of the non-blocking sequence may require taking in consideration a second point of reference.

In general, the present invention is not restricted  
5 to a particular non-blocking sequence or a particular algorithm or method for determining the non-blocking sequence given a certain network topology. The person skilled in the art will appreciate that a large number of possibilities exist, other than those presented in this  
10 specification, to establish a non-blocking sequence such that the software installation on one node does not block the software installation on another node.

Once the node sequencing entity 48 has established  
15 the non-blocking sequence, this data is passed at step 66 to the message generation entity 46.

In general, steps 66 and 64 correspond to stage 1 of the software product installation.

20

At step 68, that corresponds to stage 2 above, the message generation entity 46 will send messages to the nodes 24-30 to convey a first command. The first command directs the nodes 24-30 to fetch a catalogue of files from  
25 a file server in the data network 10. Assume for the sake of this example that the file server is implemented by the SM node 16. Here the messages are sent without following the non-blocking sequence since during the catalogue fetching operation each node 24-30 retains its message  
30 passing capability, thus one node does not block messages directed to downstream nodes. The messages conveying the first command are sent in rapid sequence to the nodes 24-30 such that the nodes are instructed at about the same time to initiate the catalogue fetching operation. The

13579ROUS01U

Page 13 of 25

Privileged &amp; confidential

catalogue fetching operation occurs concurrently on the nodes 24-30. Also, the control entity 40 starts to log relevant events. One of these events is the dispatch of the first command, and whether or not each node has  
5 acknowledged receipt and/or completion of the directives to fetch the catalogue of files.

The control entity 40 will not wait indefinitely for a node 24-30 to respond. After a timeout period, the non-  
10 responding node 24-30 is considered as "failed" and an entry to this effect is entered in the log.

At step 70, corresponding to stage 3 above, the message generation entity 46 issues messages to nodes 24-  
15 30 (except the nodes previously marked "failed") to convey a second command which directs the individual nodes 24-30 to fetch the files in the catalogue of files obtained earlier. Those files are the load files from which the software installation will proceed. As with the first  
20 command, the messages conveying the second command are sent without following the non-blocking sequence since during the files fetching operation each node 24-30 retains its message passing capability. Each node 24-30 (except any node previously identified as "failed") is  
25 expected to acknowledge the reception of the second command and/or completion of the files fetching operation. After a timeout period, nodes that have not responded are marked "failed" in the log.

30 As with the first command, the messages conveying the second command are sent in rapid sequence to the nodes 24-30 such that the nodes are instructed at about the same time to initiate the file fetching operation. The file

13579ROUS01U

Page 14 of 25

Privileged &amp; confidential

fetching operation occurs generally concurrently on the nodes 24-30.

At step 72 that corresponds to stage 4 above the message generation entity 46 issues messages to nodes 24-30 to convey a third command which directs the individual nodes 24-30 to activate the new software product. In practice, this is effected by rebooting the nodes 24-30. Since during rebooting the nodes lose their message passing capability the non-blocking sequence is followed. The message generation entity 46 will first issue a message with the third command to the node 30 only and follow with a message with the third command to the node 28 only when the node 30 has acknowledged reception of the third command. This sequence continues with the message containing the third command being sent to the node 26 and finally to the node 24. Again, any relevant events are noted in the log. In practice, all the messages containing the third command are sent over a short time period, say a few seconds, while the rebooting takes several minutes. By following the non-blocking sequence, coincident rebooting of the nodes 24-30 can be accomplished, thus allowing saving a significant amount of time.

25

For the SM 18, the sequence of the third command dispatch is as follows. The message containing the third command is sent to the nodes 34 and 36 at the same time. The sequence continues with the message containing the third command being sent to the node 32 after the nodes 34 and 36 have acknowledged reception of the third command. Finally the third command is sent to the node 31, after the node 32 has acknowledged reception of the third command.

13579ROUS01U

Page 15 of 25

Privileged &amp; confidential

At step 74 that corresponds to the stage 5 above, the message generation entity 46 issues messages to nodes 24-30 to convey a fourth command which directs the individual  
5 nodes 24-30 to commit to the new software. During the committal, the files relating to any previous version of the new software product software are erased such that the node cannot be returned to the previous version of the software product. Here the non-blocking sequence is not  
10 used since during the committal the nodes maintain their message passing capability. Evidently, the non-blocking sequence may be used if desired or if during the committal the message passing capability of the nodes is lost.

15 The software installation process is now completed and the control entity sends the log through an appropriate message to the network manager 14 such that the information in the log can be displayed to the network operator, identifying the nodes on which the installation  
20 of the software product was successful and the nodes where a failure occurred, with information about the reason of the failure.

The messages described earlier can be based on a  
25 variety of protocols. Connection oriented protocols can be used, such as Transmission Control Protocol Internet Protocol (TCPIP), Common Management Information Protocol (CMIP) and Simple Network Management Protocol (SNMP). Also connectionless protocols can be used such as User  
30 Datagram Protocol Internet Protocol (UDPIP). Other protocols can also be used without departing from the spirit of the invention.

13579ROUS01U

Page 16 of 25

Privileged &amp; confidential

Although various embodiments have been illustrated, this was for the purpose of describing, but not limiting, the invention. Various modifications will become apparent to those skilled in the art and are within the scope of  
5 this invention, which is defined more particularly by the attached claims.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000